

## **PRODUCT SPECIFICATIONS**

- ANSI 156.4 Grade 1.
- UL / UL10C Listed. 3 hour Fire Rating.
- Compliant with ADA reduced opening force requirements (4400 Series).
- 9-1/16" Horizontal Mounting Hole Pattern (5000 Series, 4400 Series).
- Universal 12" Horizontal Mounting Hole Pattern (6000 Series).
- Fully Adjustable Power Size 1~4 (4400 Series), Factory Preset Size 3.
- Fully Adjustable Power Size 3~6 (5000 Series), Factory Preset Size 3.
- Fully Adjustable Power Size 1~6 (6000 Series), Factory Preset Size 3.
- Independent Latch, Sweep, and Backcheck Intensity Valve.
  Heavy Duty Rack and Pinion. Heat treated High Tension Piston.
- High lubricity hydraulic fluid to ensure smooth operation.
- 6000-DA equipped with Delay Action feature (20 second minimum hold open delay. Easily adjusted up to 1 minute).
- Standard arm and parallel bracket included for regular arm, top jamb, and parallel arm applications.
- Standard arm installation allows door to swing 180?
- Standard full cover.
- Non Handed.

## **O**PTIONAL **F**EATURES

- Hold open arm with parallel bracket.
- Thru bolts for metal door mounting.
- Slim Cover (6000 Series).
- Drop Plates (6000 Series).

## FINISHES AVAILABLE

SYMBOL	DESCRIPTION
689	Aluminum
695	DURO
696	Gold (6000 Series Only)
	689 695