

# PURE MINERAL OILS



LUBRICATION



**TOTAL**

Process Oils.

## APPLICATIONS

- **PURE MINERAL OILS** are high quality lubricating oils used as process oils in a variety of industries. They are available in two SAE grades to meet industrial equipment lubrication needs. They are made from specially selected base stocks.
- **PURE MINERAL OILS** are primarily used as process oils in a variety of industries: rubber, plastics, textiles, processing hides or skins, and the manufacture of printing inks. They can also be used as anti-clumping agents, anti-dust agents, machine and gearbox oils, hydraulic oils and circulatory systems (in some instances). These products are also appropriate for the lubrication of non-critical mechanical parts which require a pure mineral oil containing no additives. Typically, these types of applications are "once-through" applications.

## ADVANTAGES

- Medium to low natural viscosity index.
- Perfectly suitable for blending.
- Bright and clear.
- Good lubricity.
- Non-staining.

TYPICAL CHARACTERISTICS	PURE MINERAL OILS	
	30	40
SAE Grade	30	40
Color	3.0	3.5
Viscosity at 40°C, cSt	140.0	200.0
Viscosity at 100°C, cSt	11.0	14.5
Viscosity Index	41	56
Density @ 60 °F, lbs./gal.	7.55	7.66
Specific Gravity @ 60/60 °F	0.907	0.919
Flash Point, COC, °F(°C)	410(210)	462(239)
Pour Point, °F(°C)	10(-12)	5(-15)

## TOTAL Specialties USA, Inc.

Linden, NJ 07036  
5 North Stiles Street  
1-800-323-3198  
www.totalspecialties.com

PUREMIN

7-2016

This lubricant must be applied as recommended and used for the application for which it was designed. TOTAL Specialties USA, Inc. will have no responsibility for any injury to persons or property resulting from misuse or misapplication of the lubricant. A safety data sheet conforming to the OSHA Hazard Communication Standard 29 CFR Section 1910.1200 can be downloaded at [www.totalspecialties.com](http://www.totalspecialties.com). Copyright 2016 All rights reserved.