

## Specifications:

**Cladding :** *Pressure treated* tanalised shiplap boarding 125 x 16mm (nominal).

**Framework:** *Pressure treated* 70mm x 45mm studded at 2ft centres, frames are screwed not nailed together for extra strength  
Top and bottoms separate for ease of handling.  
2.1m to eaves as standard, 2.7 to apex

**Lining to 4ft:** 11mm, 18MM OSB board or ½” Ply depending on customers’ requirements  
Dividing walls fully lined one side and 4ft the other  
Stable offer includes half height wall as standard.

**Roof trusses:** Pressure treated 95x70mm  
Internal trusses lined for strength and security.  
Galvanised hangers pre fixed approx 600mm apart.

**Purlins:** 100x50 for Onduline  
150x50 for fibre cement or preboarded roof upgrades

**Roofing:** Onduline 2m roofing sheets fixed with genuine onduline nails on each purlin line.  
Onduline ridge caps to APEX.  
3ft overhang as standard, 1.2m (4ft optional as upgrade)  
Overhang as standard lined with 11mm OSB boarding.  
**Upgrade: ETERNIT FIBRE CEMENT VERSION, CENTRED APPROX 1m.**

**Stable doors:** Fully boarded base and top door with chew strip and kick over bolt  
20mm TVG pressure treated tanalised.  
½” ply to inner braced with 150x25mm  
8” pad bolts and 6” cabin hooks.  
All fixings galvanised. Base door 4ft high, top 785mm as standard  
Stable offer only has a base door.

### Extras popular that are optional:

**Hunter ½ round guttering to front and back separate down spouts.**  
**Socialising / talkgrilles between boxes**  
**8ft Height to eaves**  
**Different coloured roofing materials**  
**Thicker kickboards up to ¾” ply.**  
**19mm shiplap**



*For a Friendly Professional Service, of the Highest Quality, at the Best Price Possible...*

Registered No 4683236, Registered Address Gardner & Co, Brynford House, Holywell