

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
510	STD	17-61	72-16	258	268	186	192	.252	.255					HYD	HYD	114	114	
437	1	20-61	63-18	261	261	194	194	.271	.271			.022	.020	HYD	HYD	108	119	POLICE GRIND
743	1	18-68	76-18	265	273	195	205	.273	.278			.026	.026	HYD	HYD	109	115	
576	2	16-71	70-17	265	268	207	209	.278	.278			.035	.031	HYD	HYD	117	117	
826	3	29-67	73-23	276	276	212	217	.306	.312			.046	.044	HYD	HYD	110	112	
805	3	24-68	77-22	272	280	214	223	.305	.310			.045	.041	HYD	HYD	114	114	
801	4	31-79	81-29	290	290	218	218	.312	.312			.041	.036	HYD	HYD	115	115	
589	5	36-68	66-36	284	282	223	227	.322	.318			.071	.071	HYD	HYD	105	105	

CODE: HOLDEN V6
 PERFORMANCE - 46GV6
 STANDARD - 46SV6
 BILLET - EPVNV6
 EXCHANGE - DEP V6

NOTES: VN-VR JOURNAL 1.785 VS JOURNAL 1.840
 SERIES 1 HAS FLANGE
 SERIES 2 HAS SMALL SNOUT
 ECOTEC HAS LARGER JOURNALS & LOBE SPACING

V6

HOLDEN