

WAGGOTT CAMS

No.	S T A G E	ADV TIMINGS		DURATION				LIFT						TAPPET CLEARANCE		LOBE CENTRE		REMARKS
				Advertised		@.050"		Cam		Valve		@T.D.C.						
		In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	In.	Ex.	
688	STD					199	198	.294	.294	.412	.412							STD-GN HYD
696	1	22-69	57-20	272	257	208	205	.292	.295	.399	.401	.043	.034	.010	.012	109	110	TORQUE & 4WD
320	1	26-68	70-26	274	276	216	216	.338	.345	.463	.469	.060	.062	.010	.014	110	110	TURBO
278	2	30-71	70-30	281	280	218	217	.335	.335	.457	.455	.070	.065	.012	.014	109	110	
106	3	35-71	71-35	286	286	222	224	.325	.345	.447	.473	.070	.065	.008	.010	108	108	
290	4	40-80	80-38	300	298	241	240	.324	.327	.444	.446	.091	.089	.010	.012	108	109	

CODE: MITSUBISHI 2/2.6 LTR
 PERFORMANCE - 44GOHC
 STANDARD - 44SOHC
 BILLET - EP107
 EXCHANGE - DEP SIG

NOTES: SIGMA AND PAJERO LATE MODEL HYD - SO CHECK
 SPRINGS TO SUIT VS6001

2/2.6 LTR

ROCKER RATIO 1.4

MITSUBISHI