

ENVIRO CHEM® NOVUS

Environmental & Safety Benefits

- Neutral pH
- Readily Biodegradable*
- No Suspected Endocrine Disruptors
- No Heavy Metal Complexes, APE's, Formaldehyde
- No Odour
- Non-Corrosive
- Non-Reactive
- Phthalate Free

Directions for Use

Floor preparation: For best results, start with a properly prepared floor by removing all of the old finish using Enviro Chem Floor Stripper according to its directions. Rinse floor thoroughly to remove all residues and allow to dry.

Application:

Do not apply product if flooring and/or ambient temperatures are less than 13°C (55°F).

- 1. If not sealed, build an adequate base for ease of maintenance with the desired floor care system by applying three (3) thin coats of Enviro Chem Novus. Allow adequate drying time between coats, typically 24°C (75°F) and 50% relative humidity requires an average of 45 minutes. Adjust drying times according to specific application conditions.
- 2. For added depth of gloss and protection, apply an additional two (2) thin coats may be applied. If applying thick coats allow 24-48 hours dry time before applying.

Maintenance

Enviro Chem Novus is an environmentally preferable zinc-free coating that may be attacked or dulled by harsh cleaners.

- 1. Daily dust mopping or sweeping will remove abrasive debris that will impact appearance and increase maintenance.
- 2. Damp mop or autoscrub using 15 ml per 4 litres (1/2 oz per gallon) of Enviro Chem Low Foam All Purpose Cleaner.
- Recommend using aqua pad with a burnishing machine, for gloss restoration.
- 4. Deep-scrub as required to maintain finish and gloss.

Coverage: Up to 3000 square feet per gallon. (295 m² per 4 Litres) (74 m² per Litre).

Slip Resistance: Meets ASTM D2047-93 requirements for slip resistance.

Product Performance Characteristics

Enviro Chem Novus creates a new standard in floor care by combining an unequaled level of environmental preference with performance, which surpasses conventional floor finish technology.

Enviro Chem Novus excels with all maintenance systems: scrub and recoat, spray buff or burnish. You'll get a tough, black-mark resistant shine with no powdering. No sealer is required on resilient flooring, even after heavy stripping.

Properties

pH	8.3-8.6
Specific Gravity	
Appearance	opaque, white, liquid
Specular Gloss (5 Coats, VCT)	79
Leveling	
Powdering	excellent
VOC (ARB 310)	<1%

Packaging

11927046 2x10 Litre Case

For handling and precautionary information, reference the product label and material safety data sheet.

For more information about RML call 1.800.387.71740 or go to www.rochestermidland.ca



This product meets Ecologo $^{\rm IM}$ Environmental Standard for Hard Floor Care Products (CCD-147) based in its low impact for human and environmental health.